



The most specified fog machine in the world. The Magnum 2000 is the authority in portable fog machines. Few other portable foggers can match the optional DMX controlled output of the Magnum 2000, or its logical plug and fog simplicity.

- 700 m³/min fog output
- 1600 W heat exchanger
- 8 min heat-up time
- Floor standing or truss mounting
- 9.5 liter fluid capacity
- Different fluid options for different applications
- DMX with optional DMX interface module
- On-board control panel
- Removable panel for remote control
- Timer and output level remote control

Physical Length: 695 mm (27.4 in.)
Width: 356 mm (14.0 in.)
Height: 325 mm (12.8 in.)
Dry weight: 13 kg (28.7 lbs.)

Performance Max. fog output (approx.): 700 m³ per minute
Max. operating time at full output (approx.): 180 minutes
Warm-up time (approx.): 8 minutes

Control and Programming Control options: Remote control (supplied), DMX with optional DMX interface module
Remote control features: Instant or timer-controlled variable output

Construction Housing: Steel & aluminum
Heat exchanger: 1500 W, direct thermal protection

Fluid System Fluid pump: Oscillating piston, high pressure
Onboard fluid capacity: 9.5 l
Fluid consumption at peak output: 95 ml per minute

Installation Orientation: Floor or flying kit

Connections Remote control: 3-pin locking XLR
0-10 V analog: 3-pin locking XLR
Power cable entry: Hard-wired

Electrical AC power (EU models): 220-240 V nominal, 50 Hz
AC power (US models): 110-120 V nominal, 60 Hz
Main fuse (220-240 V power): 10 A

Main fuse (110-120 V power): 15 A

Typical Power and Current**US model**

110 V, 60 Hz: 1570 W, 14.27 A

115 V, 60 Hz: 1716 W, 14.92 A

120 V, 60 Hz: 1868 W, 15.56 A

EU model

220 V, 50 Hz: 1319 W, 4.08 A

230 V, 50 Hz: 1442 W, 6.26 A

240 V, 50 Hz: 1570 W, 7.13 A

Measurements made at nominal voltage. Allow for a deviation of +/- 10%.

Thermal

Maximum ambient temperature (T_a max.): 40° C (104° F)

Exterior surface temperature, steady state: 50° C (122° F)

Max. nozzle temperature: 200° C (392° F)

Approvals

EU safety: EN 50 081-1, EN 50 082-1

EU safety: EN 60 335-1 (1995)

Included Items

User manual: P/N 35000038

Analogue remote control (panel mounted): P/N 90760200

Hard wired mains cable 2 m (6.6 ft.):

XLR Cable 5 m (16.4 ft.) (for remote): P/N 11820008

Container 9.5 l: P/N 34300528

Accessories

Pro Smoke Studio (DX Mix) fluid

Pro Smoke Super (ZR Mix) fluid

Pro Smoke Super (Fragranced) fluid

Pro Smoke High Density (SP Mix) fluid

I-fog fluid

Ducting Kit incl. adapter and 5 m (16.4 ft.) of 4-inch (104mm) ducting: P/N 92625006

DMX interface Magnum 2000: P/N 90758020

Ordering Information

Martin Magnum 2000, 230 V: P/N 92228000

Martin Magnum 2000, 115 V: P/N 92228100

Published on: 16 Aug 2008. © 2000-2008 Martin Professional A/S. Specifications subject to change without notice